



# **SINTRON Longlife III**

## **FULL SYNTHETIC MOTOR OIL**

### **TECHNICAL DATA SHEET**

#### **Product Description**

Veedol Sintron Longlife III SAE 5W-30, is a multi grade engine oil based on specially selected synthetic base stocks and formulated with the very latest in advanced technology, producing a super high performance engine oil which delivers excellent fuel economy.

Fully Synthetic Sintron Longlife III is suitable for use on Gasoline and Diesel engines and has been developed to provide outstanding lubrication performance for extended drain intervals. Sintron C3 is suitable vehicles with or without turbos and helps to extend the life of particle filters.

#### **Performance Specifications:**

Veedol Sintron Longlife III 5W-30 meets the performance requirements of: API SN, ACEA C3-12

OEM APPROVALS: MB-Approval 229.51 | Approved under VW 504.00/507.00| Porsche C30 | BMW Longlife-04 (LL-04)

#### **Features/Benefits:**

- 100% Fully Synthetic motor oil improves engine performance & fuel economy.
- Delivers optimum performance & engine protection at extreme temperatures & under high performance conditions.
- High level engine cleanliness & protection from combustion contamination.
- For use in gasoline and diesel engines either naturally aspirated or turbo-charged.
- Formulated for extended oil change intervals.
- Helps to extend the life of particle filters.

#### **AUTOMOBILE SOLUTIONS AMERICAS INC.**

3660 Hurontario Street, Suite 400

Mississauga, Ontario, Canada, L5B 3C4

Tel: 647 558 4500, Fax: 647 558 4499, Toll Free: 800 975 2935, E-mail : [info@asaveedol.com](mailto:info@asaveedol.com)

[www.asaveedol.com](http://www.asaveedol.com)

**THE PROFESSIONAL'S CHOICE**



# SINTRON Longlife III

## FULL SYNTHETIC MOTOR OIL

### TECHNICAL DATA SHEET

#### Typical Properties

	ASTM Method	SAE 5W-30
Density	D 4052	0.851
Kinematic Viscosity		
cSt @40°C	D 455	72.60
cSt @100°C	D 455	12.30
Viscosity Index	D 2270	172
Flash Point, °C	D 92	230
Cold Cranking Viscosity	D 5293	6000
@		(-30°C)
TBN	D 2896	7.4

Properties mentioned above are typical only and minor variations, which do not affect the product performances, are to be expected in normal manufacturing.

#### Health and Safety

Veedol Sintron Longlife III Passenger Car Motor Oil is made with highly quality synthetic base oils, polymers and premium additives. As with any petroleum product, careful handling and good hygiene should be practised. Avoid prolonged skin exposure, splashing into eyes or ingestion. For more information, please consult our Material Safety Data Sheet (MSDS) which you can find at [www.asaveedol.com](http://www.asaveedol.com)

#### AUTOMOBILE SOLUTIONS AMERICAS INC.

3660 Hurontario Street, Suite 400  
Mississauga, Ontario, Canada, L5B 3C4  
Tel: 647 558 4500, Fax: 647 558 4499, Toll Free: 800 975 2935, E-mail : [info@asaveedol.com](mailto:info@asaveedol.com)  
[www.asaveedol.com](http://www.asaveedol.com)

**THE PROFESSIONAL'S CHOICE**